

Low Loss Optical Waveguides for Astronomical Heterodyne Imaging

Principal Investigator: Mahmood Bagheri (389); Co-Investigators: Hani Nejadriahi (389), Sam Keo (389)

Program: FY22 R&TD Topics Strategic Focus Area: Nano- and Micro- Devices/Systems

Objectives:

- Develop low-loss GaAs photonic waveguides operating at long-Infrared portion of the optical spectrum (10 μm).
- Couple Quantum Well Infrared (QWIP) detectors with
 - the waveguides
 - Improve QWIP detection efficiency
 - Enhance scalability for linear detector arrays

Background:

- High angular resolution imaging requires multitelescope interferometers
 - Not possible to build single telescopes
- Heterodyning astronomical signals with a local oscillator in the mid-infrared portion of the spectrum, allows observation of stellar sizes, shapes and asymmetries with high angular resolution.
- Infrared Spatial Interferometer on Mount Wilson is a heterodyne interferometer limited by the signal-tonoise ratio due in part to the single local oscillator Optical frequency combs when used as the Local Oscillators (LOs) in these heterodyne systems offer game-changing wide bandwidth and radical simplification of the required infrastructure.

Comb enabled Heterodyne

analyzer



National Aeronautics and Space Administration Jet Propulsion Laboratory

California Institute of Technology Pasadena, California

www.nasa.gov

Clearance Number: CL# Poster Number: RPC# Copyright 2022. All rights reserved.

Approach and results:

AlGaAs/GaAs photonics

- · Platform is compatible with QWIP technology
 - · Allows for eterogenous integration
- III/V is mature and allows for easy processing

Simulated TE mode profile of a GaAs/AlGaAs heterostructure



X-ray (left) and SEM image of cross section (right) of the grown GaAs/AlGaAs heterostructure





SEM image of the fabricated waveguides (left) and optical image of the fabricated photonic chips





PI/Task Mgr. Contact Information: Email: Mahmood.Bagheri@jpl.nasa.gov